



UNI 6742 DIN 3112

- Asta di manovra scorrevole arrestabile nella posizione desiderata su tutta la lunghezza.
- Un fermo di sicurezza impedisce la fuoriuscita dell'asta per evitare incidenti.
- Triplice marcatura della misura sulla testa.

| art. | mm | L mm | Ø mm | L1 mm | A mm | A1 mm | g | |
|-----------|--------|------|------|-------|------|-------|------|------|
| 009500006 | 950 6 | 6 | 210 | 10,1 | 145 | 5,0 | 16,0 | 98 |
| 009500007 | 950 7 | 7 | 212 | 11,2 | 145 | 6,0 | 18,0 | 100 |
| 009500008 | 950 8 | 8 | 220 | 12,4 | 160 | 7,0 | 19,0 | 140 |
| 009500009 | 950 9 | 9 | 223 | 13,5 | 160 | 8,0 | 20,0 | 142 |
| 009500010 | 950 10 | 10 | 230 | 14,9 | 160 | 8,5 | 21,0 | 172 |
| 009500011 | 950 11 | 11 | 233 | 16,1 | 160 | 9,0 | 22,0 | 176 |
| 009500012 | 950 12 | 12 | 240 | 17,5 | 175 | 9,5 | 23,0 | 228 |
| 009500013 | 950 13 | 13 | 244 | 19,7 | 175 | 10,5 | 24,0 | 233 |
| 009500014 | 950 14 | 14 | 250 | 20,1 | 190 | 11,5 | 25,0 | 289 |
| 009500015 | 950 15 | 15 | 254 | 21,5 | 190 | 12,0 | 25,0 | 307 |
| 009500016 | 950 16 | 16 | 260 | 22,7 | 200 | 12,5 | 26,0 | 414 |
| 009500017 | 950 17 | 17 | 264 | 24,1 | 200 | 13,0 | 27,0 | 436 |
| 009500019 | 950 19 | 19 | 274 | 26,6 | 230 | 14,5 | 29,0 | 553 |
| 009500022 | 950 22 | 22 | 290 | 29,9 | 290 | 16,0 | 32,0 | 797 |
| 009500024 | 950 24 | 24 | 300 | 32,2 | 320 | 18,0 | 36,0 | 976 |
| 009500027 | 950 27 | 27 | 315 | 36,2 | 370 | 21,0 | 42,0 | 1265 |

